


40° MODULE SPECIFICATION SHEET



MODULE

Parameter	Value	Unit	Comment
Field of View	40°	Degree	
Binocular resolution	1280 x 720	Pixels	
Eye relief	25	mm	
Efficiency	1750	Nits/Watt	
Inter Pupillary Distance (IPD)	63	mm	
Refresh rate (Evaluation Kit only)	60	Hz	
Interface (Evaluation Kit only)	USB-C display port alt mode		
System power (Evaluation Kit only)	3	Watts	Electronics interface at default brightness
Operating temperature	5 to 55	°C	
Storage temperature	-20 to 60	°C	



WaveOptics

Disclaimer

Information in this document is provided solely in connection with WaveOptics products. WaveOptics Ltd. We reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All WaveOptics products are supplied pursuant to the terms of our module programme or bespoke customer agreement.

Nothing in this Agreement shall be construed as granting or conferring any right in, title to or licence in respect of WaveOptics confidential information or intellectual property rights, which shall remain the property of WaveOptics at all times. No warranty is given by us related to the accuracy or completeness of any confidential information and all implied warranties or representations to that effect (save for fraudulent representations) are hereby excluded.

Unless otherwise set forth in our agreement with you, WaveOptics disclaims any express or implied warranty with respect to the use of our products including without limitation implied warranties of merchantability, fitness for a particular purpose (and their equivalents under the laws of any jurisdiction), and all our products are supplied 'as is' to our customer only.

WaveOptics, 141 Park Drive, Milton Park, Abingdon, Oxfordshire OX14 4SR.

Version 1

19 August 2019

© WaveOptics 2019